

## DINGO BAMBOO FLOORING DURABAM 2-L and 3-L

### TECHNICAL DETAILS

<b>Top Layer:</b>	DURABAM 3 mm, 3-L with microbevel
<b>Execution:</b>	2-L: 1 crossed bottom layer 3-L: 2 layers bamboo, middle layer crossed
<b>Surface:</b>	finished
<b>Dimensions:</b>	920/1830 x 92/142 x 10/13 mm
<b>Colours:</b>	Honey, Marron
<b>Resistance:</b>	resistant against mould and insects *
<b>Bamboo Species:</b>	Phyllostachys Pubescens *
<b>Density Top Layers:</b>	abt. 1.05 g/cm <sup>3</sup> *
<b>Hardness Top Layers:</b>	abt. 9.5 after Brinell (95 N/mm <sup>2</sup> ) *
<b>Fire Protection Standard:</b>	EN 13501-1: Cfl-S1 *
<b>Emission Class:</b>	0.01 mg/m <sup>3</sup> (E1 Standard: <0.124 mg/ m <sup>3</sup> ) *
<b>Electrostatic Chagement:</b>	0 V/cm
<b>Underfloor Heating:</b>	2-L qualified *
<b>Moisture Content</b>	abt. (8+/-2) % *
<b>Packing:</b>	abt. 2.03/1.56 m <sup>2</sup> per Box (24/6 planks)
<b>Dimensions of Box:</b>	abt. 930/1840 x 380/150 x 70/90 mm
<b>Weight of Box:</b>	abt. 18/16 kg
<b>Time of Delivery:</b>	abt. 5 days