

DINGO Bamboo Industry Flooring

TECHNICAL DETAILS

Execution:	blocks of vertical bamboo strips hold together with tape
Surface:	unfinished
Dimension:	280 x 140 x 10/15 mm / DURABAM: 300 x 200 x 10 mm
Colours:	Bamboo Nature, Canoe Brown DURABAM: Honey, Marron
Resistance:	resistant against mould and insects *
Bamboo Species:	Phyllostachys Pubescens *
Density:	abt. 0.70 g/cm ³ / DURABAM: abt. 1.05 g/cm ³ *
Hardness:	abt. 4.0 Brinell (40 N/mm ²) * DURABAM: abt. 9.5 Brinell (95 N/mm ²) *
Fire Protection Standard:	EN 13501-1: Cfl-S1 *
Emission Class:	0.01 mg/m ³ (E1 Standard: <0.124 mg/m ³) *
Heat Conductivity:	$\lambda = 0.17 \text{ W} / (\text{m}\cdot\text{K})$
Heat-Insulating Property:	$R = 0.058 / 0.088 \text{ m}^2\cdot\text{K}/\text{W}$
Moisture Content:	abt. (8+/-2) % *
Underfloor Heating:	10 mm thickness qualified *
Packing:	3.763 / 2.352 / DURABAM: 1.92 m ² per box
Dimensions of Box:	abt. 900 (820) x 200 (320) x 175 (95) mm
Weight of Box:	abt. 26 kg / DURABAM: abt. 20 kg
Delivery Time:	abt. 5 days



Installation Information:

The Industry Flooring is glued down to the subfloor.

The surface is roughly sanded and the sanddust is mixed with putty to fill the joints. After putty has hardened the surface is sanded again and oiled or finished.