

## **DINGO BAMBOO FLOORING TIGERBAM**

### **TECHNICAL DETAILS**

<b>Wear Layer:</b>	abt. 3 mm, with microbevel
<b>Dimensions:</b>	1840 x 130 x10 mm
<b>Surface:</b>	Finished
<b>Colours:</b>	Honey with Marron
<b>Resistance:</b>	resistant against mould and insects *
<b>Bamboo Species:</b>	Phyllostachys Pubescens *
<b>Density:</b>	abt. 1.05 g/cm <sup>3</sup> *
<b>Hardness:</b>	abt. 6.77 – 8.4 after Brinell (N/mm <sup>2</sup> ) *
<b>Fire Protection Standard:</b>	EN 13501-1: Cfl-S1 *
<b>Emission Class:</b>	0.01 mg/L (E1 Standard: <0.5 mg/L) *
<b>Electrostatic Chargement:</b>	0 V/cm
<b>Underfloor Heating:</b>	qualified *
<b>Moisture Content</b>	abt. (9+/-2) % *
<b>Packing:</b>	2.39 m <sup>2</sup> per Box (10 planks)
<b>Dimensions of Box:</b>	abt. 1850 x 140 x 120 mm
<b>Weight of Box:</b>	abt. 32 kg
<b>Time of Delivery:</b>	abt. 5 days