

## DINGO BAMBOO FLOORING DURABAM 2-Layer and 3-Layer

### TECHNICAL DETAILS

<b>Top Layer:</b>	DURABAM 2-L: 4 mm, 3-L: 3 mm
<b>Execution:</b>	2-L: 1 crossed bottom layer 3-L: 2 layers bamboo, middle layer crossed
<b>Surface:</b>	Oiled, finished
<b>Dimensions:</b>	920/1830 x 96/142 x 10/13 mm
<b>Colours:</b>	Honey, Marron
<b>Resistance:</b>	Biological durability Class 5 (EN 350) *
<b>Bamboo Species:</b>	Phyllostachys Pubescens *
<b>Density Top Layers:</b>	Abt. 1.05 g/cm <sup>3</sup> *
<b>Hardness Top Layers:</b>	Abt. 9.5 kg/mm <sup>2</sup> (EN 1534) *
<b>Reaction to fire:</b>	Cfl-s1 (EN13501-1) *
<b>Emission Class:</b>	Class E1: (<0.124 mg/ m <sup>3</sup> ) (EN 717-1) Class EO (<0.025 mg/m <sup>3</sup> ) no formaldehyde *
<b>Use Class:</b>	Class 1 (EN 335) *
<b>Warm Water Underfloor Heating:</b>	2-L qualified / R = 0,059 m <sup>2</sup> ·K/W *
<b>Moisture Content</b>	Abt. (8+/-2) % *
<b>Packing:</b>	2.212 m <sup>2</sup> /1.56 m <sup>2</sup> per box (24/6 planks)
<b>Dimensions of Box:</b>	Abt. 930/1840 x 380/150 x 70/90 mm
<b>Weight of Box:</b>	Abt. 17/16 kg
<b>Time of Delivery:</b>	Abt. 6 days (except islands)