

DINGO Bamboo Industry Flooring

TECHNICAL DETAILS

Execution:	blocks of vertical bamboo strips hold together with tape
Surface:	unfinished
Dimension:	280 x 140 x 10/15 mm / DURABAM: 300 x 200 x 10 mm
Colours:	Bamboo Nature, Canoe Brown
Colours DURABAM:	Honey, Marron
Resistance:	Biological durability Class 5 (EN 350) *
Bamboo Species:	Phyllostachys Pubescens *
Density:	abt. 0.70 g/cm ³ / DURABAM: abt. 1.05 g/cm ³ *
Hardness:	abt. 4 kg/mm ² (EN 1534) *
Hardness DURABAM:	abt. 9.5 kg/mm ² (EN 1534) *
Reaction to fire:	Cfl-s1 (EN13501-1) *
Emission Class:	Class E1: (<0.124 mg/ m ³) (EN 717-1) Class EO (<0.025 mg/m ³) no formaldehyde *
Use Class:	Class 1 (EN 335) *
Heat-Insulating Property:	R = 0.059 / 0.088 m ² ·K/W
Moisture Content:	abt. (8+/-2) % *
Warm Water Underfloor Heating:	10 mm thickness qualified / R = 0,059 m ² ·K/W *
Packing:	3.763 / 2.352 / DURABAM: 1.92 m ² per box
Dimensions of Box:	abt. 900 (820) x 200 (320) x 175 (95) mm
Weight of Box:	abt. 26 kg / DURABAM: abt. 20 kg
Delivery Time:	abt. 6 days (except islands)