

## DINGO Bamboo Industry Flooring

### TECHNICAL DETAILS

<b>Execution:</b>	Blocks of vertical bamboo strips hold together with tape
<b>Surface:</b>	Unfinished
<b>Dimension:</b>	280 x 140 x 10/15 mm / <b>DURABAM:</b> 300 x 200 x 10 mm
<b>Colours:</b>	Bamboo Nature, Canoe Brown
<b>Colours DURABAM:</b>	Honey, Marron
<b>Resistance:</b>	Biological durability Class 5 (EN 350) *
<b>Bamboo Species:</b>	Phyllostachys Pubescens *
<b>Density:</b>	Abt. 0.70 g/cm <sup>3</sup> / DURABAM: abt. 1.05 g/cm <sup>3</sup> *
<b>Hardness:</b>	Abt. 4 kg/mm <sup>2</sup> (EN 1534) *
<b>Hardness DURABAM:</b>	Abt. 9.5 kg/mm <sup>2</sup> (EN 1534) *
<b>Reaction to fire:</b>	Cfl-s1 (EN13501-1) *
<b>Emission Class:</b>	Class E1: (<0.124 mg/ m <sup>3</sup> ) (EN 717-1) Class EO (<0.025 mg/m <sup>3</sup> ) no formaldehyde *
<b>Use Class:</b>	Class 1 (EN 335) *
<b>Heat-Insulating Property:</b>	R = 0.059 / 0.088 m <sup>2</sup> ·K/W
<b>Moisture Content:</b>	Abt. (8+/-2) % *
<b>Warm Water Underfloor Heating:</b>	10 mm thickness qualified / R = 0,059 m <sup>2</sup> ·K/W *
<b>Packing:</b>	3.763 / 2.352 / <b>DURABAM:</b> 1.92 m <sup>2</sup> per box
<b>Dimensions of Box:</b>	Abt. 900 (820) x 200 (320) x 175 (95) mm
<b>Weight of Box:</b>	Abt. 26 kg / <b>DURABAM:</b> abt. 20 kg
<b>Delivery Time:</b>	Abt. 6 days (except islands)

